

REBOUND RUBBER TYRED WHEELS

Rebound Rubber Tyred Wheels are non-marking, quiet and shock absorbing with a low rolling resistance. They are perfect for moving lightly loaded equipment over uneven ground, and protect the load from shocks.

They roll over small obstructions easily, and are ideal for waste bins, laundry trolleys, electrical equipment and other “handle with care” goods.



RR4077



SPECIFICATIONS

Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter	Bearing Type	Load Capacity	Wheel Code
75	30	40	8mm or 3/8"	Ball	100/80	RR3348
100	30	40	8mm or 3/8"	Ball	100/80	RR4473
100	35	48	8mm, 3/8" or 12mm	Ball	150/110	RR4077
125	30	40	8mm or 3/8"	Ball	100/80	RR5573
125	35	48	8mm, 3/8" or 12mm	Ball	150/110	RR5077
150	45	63	1/2" or 20mm	Ball	350/300	RR6677
200	45	63	1/2", 20mm or 3/4"	Ball	350/300	RR8871

ELASTIC RUBBER TYRED WHEELS

Richmond's Elastic Rubber Tyred Wheels are quiet in operation and resilient, manoeuvring well over small obstacles. They are shock absorbing, providing a cushioned ride for fragile loads, and boast a good resistance to wear and tear.

Not recommended for applications where solvents are present.



ER1006



SPECIFICATIONS

Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter	Bearing Type	Load Capacity	Wheel Code
250	50	56 offset	5/8", 3/4" or 20mm	Flange Ball	250/225	ER1006