

# TRACK WHEELS

## SINGLE FLANGE

Single flange wheels are designed to run on railway line. They are made from cast iron to suit your application, with axle shafts available.


Track wheels can be flame hardened to increase wear resistance, and are also available as drive wheels. Can be used on other sections such as RHS.



SF1099



SF697



## SPECIFICATIONS

Wheel Diameter (mm)	Rim Width (mm)	Flange Width (mm)	Flange Diameter (mm)	Boss Width (mm)	Boss Diameter (mm)	Axle Diameter	Bearing Type	Load Capacity (kg)	Wheel Code
75	45	10	100	55	Solid	20 or 25mm	Ball	750	SF399
100	25	10	120	42	40	3/4"	Plain	375	SF499
100	50	20	130	70	Solid	20 or 25mm	Ball	1300	SF492
100	25	10	120	42	40	1/2"	Ball	375	SF499
150	40	9	175	53	62	3/4" or 25mm	Plain	1000	SF699
154	50	20	192	76	Solid	25mm	Ball	2000	SF697
150	40	9	175	53	62	5/8" or 20mm	Ball	1000	SF699
200	50	14	225	64	Solid	25 or 50mm	Plain	1800	SF899
200	39	16	228	55	101	35mm	Ball	1100	SF891
200	50	14	225	64	Solid	20 or 25mm	Ball	1100	SF899
250	50	15	290	65	Solid	25 or 50mm	Plain	1800	SF1099
250	52	12	285	75	125	45mm	Ball	2400	SF1098
250	50	15	290	65	Solid	25mm	Ball	1800	SF1099
300	52	14	360	95	150	50mm	Ball	4000	SF1299

