

1000 SERIES CASTORS

A higher load capacity of up to 1000kg per castor makes this range suitable for mobile platforms, aviation trolleys, automotive assembly lines and production manufacturing plants.

These castors have the ability to be towed at 6kph by tugs and tractors.

- Cast iron and poly tyred cast iron wheels
- High tensile steel kingpin to withstand side impact loads







| * | | | | | KG | J | | J | Ī | |
|------------------|---------------|---------------|---------------|-----------------|--------------------------|----------------|--------------------------|---------------|----------------|---|
| Diameter (mm) | Width (mm) | Wheel Type | Wheel Code | Bearing Type | Load Capacity (kg) | Height (mm) | Swivel Radius (mm) | Rigid Code | Swivel Code | |
| 150 | 50 | Poly Ci | PU659 | Ball | 900 | 194 | 130 | R6339 | S6338 | 2 |
| 150 | 45 | Cast Iron | Ci601 | Ball | 1000 | 194 | 130 | R6319 | S6318 | |
| 200 | 50 | Poly Ci | PU876 | Ball | 1000 | 248 | 155 | R8069 | S8068 | 2 |
| 200 | 50 | Cast Iron | Ci852 | Ball | 1000 | 248 | 155 | R8089 | S8088 | |
| 250 | 50 | Poly Ci | PU1056 | Ball | 1000 | 300 | 180 | R1020 | S1019 | 2 |
| 300 | 50 | Poly Ci | PU1218 | Ball | 1000 | 360 | 215 | R1205 | S1204 | 2 |

R6319



Brake Options

B = Brake D = Directional Lock SLB = Swivel Lock & Brake

To order castors with Brake or 4 Way Directional Lock or Swivel Lock & Brake add B, SLB or D to end of swivel code e.g. S8088B

