### RICHMOND ROLLING SOLUTIONS

# STAINLESS ELITE BOLT CASTORS

### SUITABLE FOR WET ENVIRONMENTS FULL STAINLESS CONSTRUCTION

These castors are manufactured from grade 304 stainless steel for health and hygiene applications, such as on medical or laboratory equipment. They are also seen fitted to food carts that are frequently moved through coolrooms and steamy kitchens. This range can be hose cleaned.

- Stainless steel double ball race swivel head
- Stainless steel thread guard on 100mm and 125mm models
- Plastic thread guard on 75mm models

Diameter Width Wheel Wheel Bearing Load Height Swivel With Bolt Sw	vivel
	ode
75 30 Poly Nylon PU3345 SS Ball 80 105 70 105 12 \$33	384#
75 30 Nylon NY3321 Plain 80 105 70 105 <b>12 S3</b>	390#
75 32 Rebound Rubber RR3367 SS Ball 80 105 70 105 12 S33	391#
75 32 Elastic Rubber ER3368 SS Ball 80 105 70 105 12 S33	361#
100 27 Poly Nylon PU4439 SS Ball 100 133 90 106 12 S4	478
100 30 Nylon NY4417 Plain 100 133 90 106 <b>12 S4</b>	490
100 32 Rebound Rubber RR4367 SS Ball 100 133 90 106 12 \$44	491#
100 32 Elastic Rubber ER4368 SS Ball 100 133 90 106 12 \$44	461#
125 27 Poly Nylon PU5539 SS Ball 100 159 102 106 12 S5	578
125 30 Nylon NY5517 Plain 100 159 102 106 <b>12 S5</b>	590
125 27 Poly Nylon PU5555 Ball 100 159 - 106 <b>12 555</b>	571B
125 32 Rebound Rubber RR5367 SS Ball 100 159 102 106 12 55	591#
125 32 Elastic Rubber ER5368 SS Ball 100 159 102 106 12 55	561#

Pint



S5578

S4478B

### Ion Expanding Pintles

#### Pintles listed below suit all Stainless Elite Bolt Castors

tle	Pintle Type	Pintle Code
A B	For 19mm ID Round Tube	IPN12-P1
	For 22mm ID Round Tube	IPN12-P2
	For 28.5mm ID Round Tube	IPN12-P3
1) 2) (2)	For 19mm ID Square Tube	IPN12-P4
	For 22mm ID Square Tube	IPN12-P5
	For 28.5mm ID Square Tube	IPN12-P6

SEE page 117 FOR SOLID AND THREADED PINTLE OPTIONS

### Brake Options

B = Brake

D = Directional Lock

S4361B

To order castors with Brake add B or D to end of swivel code e.g. S5578B

ир то **100КС** сарасіту

# indicates castors not available with directional lock.


### Castor Fitting Requirements

To fit this castor to a 20mm thick base requires a 50mm x 12mm set screw. Reduction bush 100RED12100BT available to allow fitting with 10mm set screw.

These castors have a 12mm bolt hole but can be reduced to suit an 8mm or 10mm bolt with a reduction bush (top hat).



Reduction bushes available to suit 8mm fittings, code: 100RED12080BT to suit 10mm fittings, code: 100RED12100BT



1300 474 246

## sales@richmondau.com

# richmondau.com