

UTILITY SERIES BOLT CASTORS

These bolt hole mounted castors are ideal for light duty applications including wire baskets, display equipment and light trolley applications.

They feature a corrosion resistant zinc plated finish in a pressed metal construction.

- Grey rubber or black nylon wheel
- Single bolt hole frame
- Pintle fittings available for round or square tubing



S4714B

Diameter (mm)	Width (mm)	Wheel Type	Wheel Code	Bearing Type	Load Capacity (kg)	Height (mm)	Swivel Radius (mm)	With Brake (mm)	Bolt Hole Size (mm)	Swivel Code
50	20	Inst Rubber	IR2201	Ball	30	68	49	75	10	S2714
50	20	Nylon	NY900	Plain	30	68	49	75	10	S2712
75	25	Inst Rubber	IR3301	Ball	50	98	65	85	10	S3714
75	25	Nylon	NY3324	Plain	50	98	65	85	10	S3712
100	25	Inst Rubber	IR4401	Ball	70	131	90	100	10	S4714
100	25	Nylon	NY4415	Plain	70	131	90	100	10	S4712

Brake Options

B = Brake


To order castors with Brake add B to end of swivel code e.g. S4712B

Castor Fitting Requirements


Fitting this castor to a 20mm thick base requires a 40mm x 10mm set screw.

These castors have a 10mm bolt hole but can be reduced to suit an 8mm bolt with a reduction bush (top hat).

10mm hole can be reduced to 8mm



Reduction bush available to suit 8mm fittings, code: 100RED1008UTI



S2714



S3712



S4712B

Nylon expanding pintles

Pintles listed below suit all Utility Series Bolt Castors

Pintle	Pintle Type	Pintle Code
	For 19mm ID Round Tube	UTI10-P1
	For 22mm ID Round Tube	UTI10-P2
	For 28.5mm ID Round Tube	UTI10-P3
	For 19mm ID Square Tube	UTI10-P4
	For 22mm ID Square Tube	UTI10-P5
	For 28.5mm ID Square Tube	UTI10-P6
	Single Bolt Fitting 10mm Various Bolt Lengths Available	

