

# ZINC DUROLITE BOLT CASTORS

This series is commonly used on a vast array of mobile equipment in hospitals, retail environments and general industry. A twin swivel race ensures longevity and enhances overall performance. These castors are available with a single bolt hole mount or a baseplate mount.

- · Large variety of wheel types
- Baseplate frame or single bolt hole frame
- Available with brake




## Nylon Expanding Pintles

#### Pintles listed below suit all Utility Series Bolt Castors

Pintle	Pintle Type	Pintle Code
	For 19mm ID Round Tube	OBT12-P1
	For 22mm ID Round Tube	OBT12-P2
	For 28.5mm ID Round Tube	OBT12-P3
	For 19mm ID Square Tube	OBT12-P4
	For 22mm ID Square Tube	OBT12-P5
	For 28.5mm ID Square Tube	OBT12-P6
	·	

SEE page 117 FOR SOLID AND THREADED PINTLE OPTIONS







# **Brake Options**

B = Brake

D = Directional Lock

To order castors with Brake or Directional Lock add B or D to end of swivel code e.g. S6080B


indicates castors not available with directional lock.

### **Castor Fitting** Requirements

To fit this castor to a 20mm thick base requires a 50mm x 12mm set screw. Reduction bush 100RED1210OBT available to allow fitting with 10mm set screw.

These castors have a 12mm bolt hole but can be reduced to suit an 8mm or 10mm bolt with a reduction bush (top hat).

> 12mm hole can be reduced to 8mm or 10mm



Reduction bushes available to suit 8mm fittings, code: 100RED12080BT

to suit 10mm fittings, code: 100RED12100BT

