

# CROWNED POLY TYRED ALUMINIUM CENTRED WHEELS

UP TO  
**600KG**  
CAPACITY








Crowned polyurethane wheels offer a much lower rolling resistance compared to traditional flat treaded wheels. They are constructed from a quiet running polyurethane tyre around a lightweight aluminium centre.

They have a high resistance to chemicals and abrasive wear, and feature precision ball bearings for extended bearing life.

- Lower rolling resistance
- Quiet running
- High resistance to chemicals & abrasive wear



PU807

 Wheel Diameter (mm)	 Tyre Width (mm)	 Boss Width (mm)	 Axle Diameter	 Bearing Type	 Load Capacity (kg)	 Wheel Code
100	50	63	1/2" or 20mm	Ball	300	<b>PU407</b>
125	50	63	1/2" or 20mm	Ball	400	<b>PU507</b>
150	50	63	1/2" or 20mm	Ball	500	<b>PU607</b>
200	50	63	1/2" or 20mm	Ball	600	<b>PU807</b>



PU407

## HEAVY INDUSTRIAL CASTORS WITH CROWNED POLY WHEELS

Castors with **Swivel Lock & Brake** or **Directional Lock** also available



S4274

R4275

S5274

R5275

S6274

R6275

S8274

R8275

## 500 SERIES CASTORS WITH CROWNED POLY WHEELS

Castors with **Swivel Lock & Brake** or **Directional Lock** also available



S4246

R4247

S5246

R5247

S6020

R6021

S8020

R8021