

## **PNEUMATIC WHEELS** PLASTIC CENTRED

Plastic centred pneumatic wheels feature a quality corrosion and rust resistant plastic rim, making them ideal for applications in wet or damp environments. They are suitable for use on nursery trolleys, hand trucks, agricultural equipment and more. They are an economical alternative to steel-rimmed pneumatics.

- Plastic rim for use in wet or damp environments
- Diameters ranging from 150mm to 400mm









**UP TO 200**KG CAPACITY

PN1610

		PN6125
4	<b>—</b>	
<b>(Q)</b>	#	7
Nom Wheel	Tyre	Во

<b>\oldot</b>	Ŧ	<b>*</b>	<b>3</b>
Nom Wheel Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter
150	29	34	1/2"
160	50	50	1/2"
215	60	62	5/8", 3/4"
215	60	62	5/8, 3/4", 20mm
265	88	60	5/8", 3/4", 20mm
265	88	60	5/8 or 3/4", 20mm
420	150	106	1"
420	150	106	20mm, 25mm, 1", 3/4"
400	100	105	1"
400	100	105	20mm, 25mm, 1", 3/4"

Bearing Type	Tyre Size	Tyre Tread Pattern	
Ball	-	-	
Ball	-	-	
Nylon Bush	2.50-4	Lug	
Flange	2.50-4	Lug	
Nylon Bush	4.10/3.50-4	Diamond	
Flange	4.10/3.50-4	Diamond	
Nylon Bush	16x6.50-8	Turf	

16x6.50-8

4.00-8

4.00-8

	KG KG	
Tyre Tread Pattern	Load Capacity (kg)	Wheel Code
-	60	PN6125
-	60	PN6200
Lug	100	PN8864
Lug	100	PN8865
Diamond	100	PN1074
Diamond	100	PN1075
Turf	200	PN1604
Turf	200	PN1610
Knobby	200	PN1603
Knobby	200	PN1627

## **Tread Types**









Flange

Nylon Bush

Flange Ball



PN1610 in use on a Richmond